



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2000054825 A**(43) Date of publication of application: **22.02.00**

(51) Int. Cl.

F01N 3/08
B01D 53/94
B01J 21/16
B01J 23/34
B01J 23/58
B01J 23/78
B01J 23/89
B01J 29/44
B01J 33/00
F01N 3/10
F01N 3/24

(21) Application number: **10224151**(22) Date of filing: **07.08.98**(71) Applicant: **NISSAN MOTOR CO LTD**

(72) Inventor: **NAKAMURA MASAKI**
SUGA KATSUO

(54) SULFUR POISONING RESISTANT NOx
OCCLUDING MATERIAL, AND EXHAUST GAS
PURIFYING CATALYST AND EMISSION
CONTROL SYSTEM USING THIS

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a sulfur poisoning resistant NOx occluding material hardly poisoned by sulfur and capable of suppressing a reduction in NOx absorbing and releasing action by laminating, on a fire resisting inorganic carrier, an inner layer and outer layer containing specified components, respectively, in a prescribed weight ratio, and using a noble metal component as occasion demands.

SOLUTION: An inner layer and a surface layer are

successively laminated on a fire resisting inorganic carrier. The inner layer contains an element M whose generating free energy changing value ($\approx G$) of $dMp(SO_4)_q$ is -350 kJ/mol or less in a reaction represented by the reaction expression: $aO_2 + bSO_2 + cMxOy \rightarrow dMp(SO_4)_q$ (wherein M represents one element selected from alkali metal and others, $MxOy$ represents the oxide of the M, $Mp(SO_4)_q$ represents a sulfate of the M, (a)-(d) each represent coefficients, and (q) represent the quantity satisfying the valency of the M). The surface layer contains the element M having ΔG larger than -350 kJ/mol . Further, the weight ratio of the inner layer to the surface layer is set to 1:3-3:1.

COPYRIGHT: (C)2000,JPO